

P R O D U C T B U L L E T I N

High Alkaline Granular Degreaser

Heavy Duty Powder Degreaser



Tennant Company • 701 North Lilac Drive • Minneapolis, MN 55442
 800-553-8033 • www.tennantco.com
 © Tennant Company 03-02-2011

DESCRIPTION:

Tennant *True* High Alkaline Granular Degreaser is a low foaming high performance powder degreaser, specifically formulated for use in Tennant scrubbers.

USES:

- Heavy duty cleaning
- Can be used on both urethane or epoxy coated floors and uncoated floors
- Heavy manufacturing facilities
- Facilities with petroleum and grease

ADVANTAGES:

- Low foaming
- Designed specifically to be used with an automated scrubber and not damage critical parts of the machine.

STORAGE: Materials should be stored indoors between 65°F (18°C) and 90°F (32°C).

SHELF LIFE: 1 year from date of manufacture.

PACKAGING OPTIONS / PART NUMBERS:

22 pound carton (10 – 2.2 lb individual bags) / 9006782
 250 pound drum / 9006783

LIMITATIONS:

- Do not use on acrylic floor finish typically applied to VCT
- Do not use if soft metal filings are being picked up by scrubber

MATERIAL PROPERTIES (POWDER):

Property	Results
Color	White
Elemental Phosphate	None
Flash Point °F/C Seta Closed Cup	N / A
Foam	Low
Form	Powder
Freeze Point	N / A
Freeze/Thaw	Passes standard test of 3 freeze/thaw cycles
Odor	Soap
pH at 4 cups / 30 gal	12.3
pH at 4 cups / 15 gal	12.5
Solubility (Tap Water)	Soluble in water
Viscosity	Water thin
Wt. Per Gallon	17.53 lb/ gal.
Wetting Agents	Nonionic Surfactants

**DILUTION GUIDE FOR
TENNANT AUTOMATIC SCRUBBERS:**

LIGHT CLEANING:

Use 1 – 2.2lb bag or 4 cups per 30 gallons of warm water

HEAVY CLEANING:

Use 1 – 2.2lb bag or 4 cups per 15 gallons of warm water

Do not exceed 1 – 2.2 lb bag or 4 cups per 15 gallons of water dilution. If increased soil removal is needed, explore additional brush / pad changes.

IMPORTANT: READ AND FOLLOW ALL PRECAUTIONS AND INSTRUCTIONS BEFORE PROCEEDING.

PLEASE SEE MATERIAL SAFETY DATA SHEET (MSDS) FOR SAFETY INFORMATION AND PRECAUTIONS.

