Click the model number below...

1510 (battery)

1530 (cord-electric)





Model 1510 Specifications

AUTOMATIC CARPET EXTRACTOR

| Feature | | English / Metric |
|---|------------|---|
| Brush System | | · · |
| Brush length | | 19-inch/ 482 mm |
| Brush type | | Nylon |
| Brush RPM | | 2800 |
| Motor power | | (2) 0.2 hp/ 0. 15 kW |
| Motor RPM | | 1800 |
| Drive System | | |
| Top interim cleaning speed | | 100 fpm/ 30 mpm |
| Top deep cleaning speed | | 50 fpm/ 15 mpm |
| Max. ramp while cleaning | | 5 degree |
| Productivity | | |
| Theoretical max. per hour: interim cleaning | | 11,000 ft²/ 1,022 m² |
| Deep cleaning | | 5,500 ft²/ 511 m² |
| Machine Dimensions | | |
| Length | | 50-inch / 1270 mm |
| Machine Width | | 22-inch / 558 mm |
| Height | | 42-inch / 1066 mm |
| Weight (batteries installed) | | 656 lb / 298 kg |
| Solution & Recovery Syst | tem | |
| Solution tank capacity | | 21 gallon/ 72 liter |
| Recovery tank capacity | | 21 gallon/ 72 liter |
| Airflow | | Dual 69 cfm/ 1.96 m³ vac motors |
| Waterlift | | (2) 68-inch/ 1727 mm vac motors |
| Vacuum motor power | | (2) 0.89 hp/ 0.66 kW vac motors |
| Vacuum motor stages | | (2) 3 stage vac motors |
| Power Consumption | | |
| Total power consumption | | 55 amps |
| Battery run time | | 3 hours |
| Battery configuration | | 4-6 volt 235 AH batteries |
| Sound Level | | |
| Operator's ear | | 72 dBa |
| Warranty | ROTATIONAL | HRS ON PARTS AND LABOR. 10 YEARS ON LY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE DMPANY FOR MORE WARRANTY INFORMATION. |





Model 1530 Specifications

AUTOMATIC CARPET EXTRACTOR

| Feature | English / Metric |
|---|--|
| Brush System | |
| Brush length | 19-inch/ 482 mm |
| Brush type | Nylon |
| Brush RPM | 2800 |
| Motor power | 0.25 hp/ 0. 19 kW |
| Motor RPM | 1800 |
| Drive System | |
| Top interim cleaning speed | 100 fpm/ 30 mpm |
| Top deep cleaning speed | 50 fpm/ 15 mpm |
| Max. ramp while cleaning | 5° |
| Productivity | |
| Theoretical max. per hour: interim clea | |
| Deep cleaning | 5,500 ft²/ 511 m² |
| Machine Dimensions | |
| Length | 50-inch / 1270 mm |
| Machine Width | 22-inch / 558 mm |
| Height | 42-inch / 1066 mm |
| Weight | 395 lb / 180 kg |
| Solution & Recovery System | |
| Solution tank capacity | 30 gallon/ 113.6 liter |
| Recovery tank capacity | 21 gallon/ 72 liter |
| Airflow | 99 cfm/ 2.80 m³ per min |
| Waterlift | 117-inch/ 2971 mm |
| Vacuum motor power | 1.63 hp/ 1.22 kW |
| Vacuum motor stages | Single 3 stage |
| Power Consumption | |
| Total power consumption | 14 amps |
| Sound Level | |
| Operator's ear | 72 dBa |
| Warranty ROTA | RS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON TIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE ACT COMPANY FOR MORE WARRANTY INFORMATION. |