




# MODEL 8200/8210 SWEEPER/SCRUBBERS SPECIFICATIONS



## Propelling System

Speed forward	6 mph	(9.6 km/h)
Speed reverse	3 mph	(4.8 km/h)
Gradeability		
Full hopper	6.0 deg	(10.5%)
Empty hopper	8.0 deg	(14.0%)

## Sweeping System

Cleaning path	50 in	1270 mm
Main brush length	36 in	915 mm
Side brush diameter	23 in	585 mm
Hopper volume	7.8 ft <sup>3</sup>	220 L
Hopper weight capacity	350 lb	160 kg
Filter area	63 ft <sup>2</sup>	5.9 m <sup>2</sup>

## Scrubbing System

Cleaning path: MaxPro 1000	40 in	1020 mm
Cleaning path: MaxPro 1200	48 in	1220 mm
Side shift: (option on 8200)	5 in	125 mm
Solution tank	52 gal	195 L
Recovery tank	52 gal	195 L

## Power Plants

Liquid gasoline/LPG	53 hp	(39.5 kW)
Liquid cooled diesel	37.5 hp	(28 kW)

## Tennant Value-Added Equipment

### Model 8200

- Multi-level dump
- Corrosion-resistant hopper, tanks
- Perma-Filter
- InstantAccess filter change
- Wet sweep bypass
- No-tool brush & squeegee change
- Power steering
- TrueTrack™ squeegee

### Optional Equipment

- Audio visual backup alarm
- Light packages
- ES Plus Solution recycling
- MaxPro 1200 scrub head
- Heavy duty bumper
- Sidebrush dust control

### Additional 8210 equipment

- LCD system display
- Service interval reminder
- One-button sweeping
- Multi-lingual messaging
- SuperScrub mode
- Automatic filter shaking
- Automatic startup diagnostics
- Edge scrubbing

- Overhead guard
- Squeegee wand
- Non-marking tires
- Suspension seat
- Fire extinguisher
- Positive drain control