



3M[™] FLOOR PAD SELECTION GUIDE FOR NOBLES® SS300

Nobles SS300 floor scrubbers have multiple machine head types to optimize cleaning performance for specific areas. 3M™ Floor Pads offer application specific choices for stripping, scrubbing and cleaning.

SINGLE DISK		DUAL DISK	ORBITAL
17" SINGLE DISK: (1) 17"/43cm pad 20" SINGLE DISK: (1) 20"/50cm pad		24" DUAL DISK: (2) 12"/30cm pads	20" ORBITAL: (1) 14" x 20"/35cm x 50cm pad
		0	

MAINTENANCE FOR FLOORS WITH CONVENTIONAL COATED FINISHES

Stripping Removes all layers of floor finish when used with a floor stripper chemical.	Scrubbing Removes 1–4 coats of finish with water or neutral cleaner. Leaves a clean surface ready for recoating.	Cleaning Designed for daily use to help remove surface soils without dulling surface. 3M™ Red Buffer Pad 5100*	
3M™ High Productivity Pad 7300*	Scotch-Brite™ Surface Prep Pad*		
 Our most aggressive stripping pad For fast finish removal and consistent stripping Open construction resists loading and clogging 	Removes 2-4 coats of finishFor heavy duty scrubbing before recoating	Designed for everyday cleaning and light scrubbing Removes light soil, scuff marks and black heel marks	
3M™ Brown Stripper Pad 7100	3M™ Blue Cleaner Pad 5300	3M™ White Super Polish Pad 4100	
Conformable stripping pad for uneven floors For stripping prior to refinishing	Removes 1-2 coats of finish For heavy duty scrubbing before recoating	For light cleaning with minimal dulling of finishHelps remove soil and scuff marksCan also be used to polish wood floors	
PROCEDURE 1. Dust mop 2. Mask off delicate surfaces 3. Apply properly diluted stripping solution 4. Let solution dwell per instructions 5. Strip with floor machine and pad 6. Pick up dirty solution 7. Detail damp mop 8. Let dry and dust mop before applying finish	PROCEDURE 1. Dust mop 2. Use properly diluted scrubbing solution 3. Scrub with floor machine and pad 4. Pick up dirty solution 5. Detail damp mop 6. Let dry and dust mop before applying finish	PROCEDURE 1. Dust mop 2. Use properly diluted cleaning solution 3. Clean with floor machine and pad 4. Pick up dirty solution 5. Let dry before buffing or burnishing	

^{*}Recommended for most applications. For softer materials such as rubber or sheet vinyl, follow flooring manufacturer's recommendations.

MAINTENANCE FOR UNCOATED POROUS STONE FLOORS TERRAZZO · MARBLE · POLISHED CONCRETE**

Polish and Restore			Alternative Method	Cleaning and Polishing
STEP 1	STEP 2	STEP 3	Scotch-Brite™ Sienna Diamond Floor Pad Plus	Scotch-Brite™ Purple Diamond Floor Pad Plus
3M™ Trizact™ Diamond HX Discs Gold	3M™ Trizact™ Diamond HX Discs Red	3M™ Trizact™ Diamond HX Discs Blue		
 Coarse abrasive For heavily damaged floors with visible wear or scratches 	• For floors with less damage • For floors with less damage • For final polishing before burnishing with Scotch-Brite™ Purple Diamond Floor Pad Plus • For final polishing other porous stone flooring • Use before Scotch-Brite™ Purple Diamond Floor Pad Plus to bring floor to a medium	Use before Scotch-Brite™ Purple Diamond Floor Pad Plus to bring floor to a medium shine	Diamond-coated pad for periodic maintenance For use with low and high speed equipment Helps bring floors to a high shine	
			if 3M™ Trizact Diamond HX Discs are not used during the restorative process	3M™ Red Buffer Pad 5100*
				Designed for everyday cleaning and light scrubbing Removes light soil, scuff marks and black heel marks

^{**} For detailed instructions on use, visit www.3m.com/facility

DISCLAIMERS:

Product Use: Many factors beyond $3M^{\text{TM}}$'s or Nobles's control and uniquely within user's knowledge and control can affect the use and performance of a $3M^{\text{TM}}$ product in a particular application. Given the variety of factors that can affect the use and performance of a $3M^{\text{TM}}$ product, user is solely responsible for evaluating the $3M^{\text{TM}}$ product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy and Disclaimer: Many factors beyond 3M™s or Nobles's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M™ product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M™ product packaging or product literature, 3M™ warrants that each 3M™ product meets the applicable 3M™ product specification at the time 3M™ ships the product. 3M™ MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M™ product does not conform to this warranty, then the sole and exclusive remedy is, at 3M™s option, replacement of the 3M™ product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, neither 3M™ or Nobles will be liable for any loss or damage arising from the 3M™ product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.