

# V-WA-30 | WIDE AREA VACUUM



**Reliable performance and increased productivity at a lower total cost of ownership.**

## Maximum productivity

This durable wide area vacuum cleans large carpeted areas with nearly four times the productivity over traditional upright vacuums.

## Reliable durability

Major components have been proven in commercial application for over five years. Low acquisition and consumable prices combined with proven performance make it easy to choose this vacuum over similar models in the market today!

## Proven performance

Standard with HEPA 4-stage filtration for improved air quality, the vacuum's cleaning performance is also certified Bronze by the Carpet and Rug Institute's (CRI) Seal of Approval program. Operating at below 70 dBA, this vacuum is also LEED qualifying.



## Key Product Features

- Increased ease of use with a fully adjustable handle that can be set to the perfect height for operator use yet folded down for easy storage when not in use.
- Easily clean hard-to-reach areas with a low profile design that provides increased maneuverability and reach under.
- Increase operator ease-of use and decrease training with easy-one button operation.

# V-WA-30 | WIDE AREA VACUUM



FEATURES	SPECIFICATIONS*
<b>Product Name</b>	V-WA-30
<b>Vacuum System</b> Airflow at orifice Vacuum motor hp Vacuum motor type Water lift at sealed orifice	226 cfm / 6.4 m <sup>3</sup> /m 1 hp / 0.75 kW each (2) 1 hp motors 12.6A / 1512 W 71 in / 1804 mm
<b>Brush Drive System</b> Brush belt description Brush Length Brush motor hp Brush motor RPM	Poly-V belt drive 30 in / 762 mm 0.25 hp / 0.19 kW 1800 rpm
<b>Filtration</b> Filtration system description Vacuum bag description Vacuum bag capacity	3-ply filter bag, washable foam intake filter, 3M Filtrete®, vac motor filter Cloth bag standard, optional paper bags (filtration at 99.9 @.3 microns) 1.6 bushel / 2.0 ft <sup>3</sup> / 0.06 m <sup>3</sup>
<b>Productivity</b> Maximum coverage rate Cleaning width	14000 ft <sup>2</sup> /hr / 1300 m <sup>2</sup> /hr 30 in / 762 mm
<b>Chassis/Body Construction</b> Construction Base	Rotationally-molded polyethylene PPO/Polystyrene blend
<b>Power System</b> Power cord length Power cord type Total power consumption	75 ft / 23 m 14 gauge, 3-wire, STJ safety yellow 14A
<b>Accessories</b> Standard	One cloth bag and two disposable paper bags
<b>Dimensions / Weight / Sound Level</b> Height Width Length Weight Sound level (at operator's ear)	39.75 in / 1009 mm 30.5 in / 775 mm 36 in / 914 mm 95 lb / 43.09 kg <70 dBA
<b>Approvals</b>	UL, CRI SOA Bronze
<b>Warranty</b>	See your sales representative or authorized distributor for complete warranty details.

\*Specifications subject to change without notice