

# Self Contained Extractor EX-SC-1020



**Sleek design, reliable performance  
in a self contained carpet extractor.**

This carpet extractor allows for the exact amount of agitation to remove tough soil without causing damage. The ergonomic handle grip and fingertip solution controls minimize hand movement during operation and allow for hours of comfortable operation. The brush meter allows the operator to adjust for optimal brush height.



**Durable construction, reliable performance**

Constructed of durable polyethylene that resists dents and cracks, this extractor is built to last and can withstand the demands of everyday extracting.

**Greater maneuverability**

This extractor is perfect for cleaning in confined areas like classrooms, office buildings, hospitals and restaurants as well as larger open areas.

## Key Benefits

- Brush scrub deck with large motor and stiff brush coupled with dual spray nozzles provide outstanding cleaning performance
- Ergonomic handle with trigger solution control allows for comfortable operation
- This unit moves easily with its lightweight yet durable construction and low center-of-gravity bladder system



# Self Contained Extractor

## EX-SC-1020



Features	Specifications*	
<b>Product Name</b>	EX-SC-1020	
<b>Vacuum System</b>	Vacuum motor HP Vacuum motor stages Water lift at sealed orifice Airflow through 2 in / 50 mm orifice Vacuum shoe size	1.8 hp / 1.34 kW 3 stage 136 in / 3500 mm 95 cfm / 2.7 m <sup>3</sup> /min 20 in / 510 mm
<b>Recovery System</b>	Recovery tank capacity Recovery tank description	14.5 gallon/ 55 L Integrated bladder tank
<b>Brush Drive System</b>	Brush motor amp Brush RPM Brush motor RPM Brush width Brush bristle type Brush diameter	1.5 A 1200 1800 17 in / 431 mm Offset rows of nylon bristles in a chevron pattern 3.31 in / 84 mm
<b>Solution System</b>	Solution pump amps Solution pump pressure Solution pump voltage Solution capacity Solution pump pressure Solution flow Solenoid valve Spray jets	1 A 100 psi / 6.9 Bar 120 V 10 gal / 38 L 100 psi / 6.9 Bar 1 gpm / 3.78 L / min Electric 2 - quarter turn, quick disconnect
<b>Total Power Consumption</b>	14.5 Amps / 1740 Watts	
<b>Power Cord</b>	Power cord length Power cord type	50 ft / 15.24 m (detachable) 16 gauge, safety yellow
<b>Optional Accessories</b>	Wands, hand tools, solution and recovery hoses, etc. Contact your sales rep for more information.	
<b>Dimensions/Weight/Sound Level</b>	Length/Width/Height/Weight/Sound	L: 43 in / 1092 mm, W: 20 in / 508 mm, H: 34 in / 863 mm, Wt: 106 lb / 48.2 kg, 78 dBA
<b>Approvals</b>	CRI-Bronze Seal of Approval, ETL	
<b>Warranty</b>	See your sales representative or authorized distributor for complete warranty details.	

\*Specifications subject to change without notice