


**SPECIFICATIONS**

**Speed Scrub™ 2701/3301 with FaST™**  
Walk-Behind Floor Scrubber




Features	Specifications (English/Metric)	
	Speed Scrub 2701	Speed Scrub 3301
Product Number	Standard – 608696 FaST-equipped – 614163	Standard – 608276 FaST-equipped – 614164
<b>Productivity</b>		
Theoretical cleaning rate	27,000 ft <sup>2</sup> / 2508 m <sup>2</sup> per hour	33,000 ft <sup>2</sup> / 3066 m <sup>2</sup> per hour
Estimated actual cleaning rate	17,606 ft <sup>2</sup> / 1636 m <sup>2</sup> per hour	21,831 ft <sup>2</sup> / 2028 m <sup>2</sup> per hour
Cleaning width	27 in / 68 cm	33 in / 83 cm
<b>Chassis/Body Construction (Rotationally-molded polyethylene)</b>		
Caster diameter	(2) 4 in/10 cm diameter x 1-1/2 in/3.8 cm	
Wheel diameter	(2) 8 in/20 cm diameter x 3-7/8 in/10 cm	
<b>Solution System</b>		
Solution tank capacity	27 gal / 102 L	
Maximum solution flow rate	.87 gpm – 3.29 L/min	
<b>Recovery System</b>		
Recovery tank capacity	27 gal / 102 L	
Squeegee width	39.5 in / 100 cm	42 in / 107 cm
Airflow	69 cfm / 1.95 m <sup>3</sup>	
Waterlift	68 in / 172.72 cm	
Vacuum motor type	5.7 in / 14.5 cm diameter; tangential discharge	
Vacuum motor HP	0.75 hp	
Vacuum motor amps	21 A	
Vacuum motor stages	3 stage	
Vacuum motor voltage	24 V	
Vacuum motor watts	550 watts	
<b>Brush/Pad System</b>		
Brush/pad diameter	(2) 14 in / 35.5 cm	(2) 17 in / 43 cm
Motor amps	20 A	
Motor HP	0.75 hp	



## SPECIFICATIONS

# **Speed Scrub™ 2701/3301 with FaST™** Walk-Behind Floor Scrubber



Features	Specifications (English/Metric)	
Motor voltage	24 V	
Motor RPM	220 rpm	
Brush/pad pressure	100 lb / 46 kg and 150 lb / 70 kg	
<b>Battery System</b>		
Battery amp hour rating	305 A	
Battery count	4	
Battery description	6 V deep cycle	
Battery run time per charge	4 hours	
Charging unit description	24 V / 25 amp automatic charger	
<b>Sound Level</b>	75 dBa @ operator's ear 70 dBa @ 10 ft	
<b>Dimensions</b>		
Product height	41 in / 104 cm	
Product length	59 in / 150 cm	
Product width	29 in / 74 cm	35 in / 89 cm
Product weight	583 lb / 264 kg 765 lb/ 352 kg (with batteries)	
<b>Warranty</b>	The warranty of this unit shall be a minimum of 10-years on rotationally-molded polyethylene housings and parts to be free from defects and workmanship under normal use and service. The non-polyethylene parts shall have a minimum of a three (3) year warranty under normal use and service. This unit shall also include service labor coverage of warranty items for a minimum of three (3) years.	

