



NAUTILUS-E Industrial Scrubber

Front Wheel Steering and High Traction Tire

Less slipping than conventional rear steer machines.



80.00" (height to top of overhead guard)

58.12" (height to the top of the steering wheel)

85.50" (length)



Productive Clean a 9ft aisle in 2 passes (55" with side scrubbing brush).



Safe Eyes forward operator design, standard LED front and rear lights.



Efficient Single pass scrubbing provides superior results.

Safety Features and Common Options

- Suspension Seat with Armrest
- Overhead Guard, Flashing Light and Front Facing Blue Light (Rear Blue, Back-Up Alarm and Red Side Marking lights available)
- Easy Access Removable Front Hood
- Standard Green One-Touch
 All Function Button
- Simple to Empty and Refill, Full View 104 Gallon Recovery Tanks













61.75"

(width)

NAUTILUS-E Industrial Scrubber 🗲

The PowerBoss Nautilus-E is the most productive and cost effective option when moving from internal combustion to battery power. The average cost is \$2.87 to fully charge Lithium Ion battery for 8+ hours of continuous operation.

INTERGRATED CLEANING SYSTEM					
Scrubbing Path (main scrub deck) With scrubbing side brush	45 in / 1,143 mm 55.5 in / 1,409.7				
Cylindrical Brush Speed	500 rpm				
Cylindrical Brush Down Force (up to)	400 lb / 181 kg				
Cylindrical Debris Hopper	0.7 ft3 / 20 Liters				
Disk Brush Speed	315 rpm				
Disk Brush Down Force (up to)	400 lb / 181 kg				
Solution Tank	90 gal / 341 L				
Recovery Tank	104 gal / 394 L (including demister chamber)				
Vacuum Fan Power	(2) @ .8 hp				
Vacuum Fan Speed	14,500 rpm				
Vacuum water lift	65 in / 1,650 mm				
PROPELLING SYSTEM					
Propel speed forward (transport variable to) Propel speed forward (scrubbing variable to)	5.5 mph 8.9 kph - 4 mph / 6.4 kph				
Dual Force Gradeability – Working	3 degrees/5%				

9.7 degrees/17%

*sweep	honner	must h	10	lifted	nrior to	anina	on a	50	ramn
Sweep	Hopper	must r	16	mileu	prior to	guing	UII a	0	ramp

Transport

Standard Battery	750 AH C6
Optional Battery (opportunity charge capable)	840 AH C6
Optional Battery (opportunity charge capable)	864 AH Lithium
MACHINE SPECIFICATIONS	
Length Basic Machine	85.5 in / 2,172 mm
Width, Body	55 in / 1,397 mm
Width, Including Side Scrub	61.75 in / 1,568 mm
Height (top of steering wheel)	58.12 in / 1,476 mm
With Overhead Guard	80 in / 2,032 mm
Minimum Aisle Turn	94.75 in / 2,407 mm
Ground Clearance	2.5 in / 64 mm



Battery Box Dimension: 38.13"x 30.56"x 17.38" (L x W x H)

Standard Wet Lead

- 750 AH included with machine
- 6 hour runtime

Thin Plate Pure Lead (TPPL)

- Compatible with Nautilus E
- ► Fast Charging
- Full 3 Shift Runtime w/opportunity charge

Lithium Ion

- Compatible with Nautilus E
- Flux Power UL certification
- 8+ hours of continuous runtime
- Up to 10-year warranty









