

SPEED SCRUB® 350 | STAND-ON SCRUBBER



Product Specifications

| Feature | 20 in / 500 mm Single Disk Self Propel | 24 in / 600 mm Dual Disk Self Propel |
|--|---|---|
| Cleaning Tool Attachment | 3-Lug Standard / Insta-Click™ Optional | |
| Machine Speed Top Scrub and Forward Transport Top Reverse Transport | 3.6 mph (5.8 km/hr) 1.1 mph (1.8 km/hr) | |
| Scrubbing Coverage Rate Per Hour Theoretical Max Conventional - Practical ec-H2O NanoClean® - Practical | 31,680 ft2 (2,946 m2) 24,588 ft2 (2,287 m2) 25,284 ft2 (2,351 m2) | 38,016 ft2 (3,535 m2) 30,052 ft2 (2,795 m2) 30,903 ft2 (2,874 m2) |
| Control Panel | | |
| Pro-Membrane™ | Standard | |
| LCD Pro-Panel® Touch Screen | Optional | |
| Brush/Pad Drive System | | |
| Cleaning Path | 20 in / 500 mm | 24 in / 600 mm |
| Pad/Brush RPM | 215 rpm | 275 rpm |
| Pad/Brush Down Pressure | 62 & 90 lbs (28 & 41 kg) | 64 & 91 lbs (29 & 41 kg) |
| Scrub Motor | 24 VDC, 0.87 HP / 0.65 kW | |
| Solution and Recovery Systems | | |
| Solution Tank Capacity | 14.1 gal (53 L) | |
| Recovery Tank Capacity | 18.4 gal (70 L) | |
| Drive Motor | 24 VDC, 0.64 HP / 0.48 kW | |
| Vacuum Motor | 24 VDC, 0.62 hp / 0.46 kW | |
| Vacuum Water Lift | 42 in (1,067 mm) | |
| Cleaning Technology | | |
| Conventional | Standard | |
| ec-H2O NanoClean® Technology | Optional | |
| Conventional Water Flow | 0.15 / 0.35 / 0.50 gpm 0.57 / 1.32 / 1.89 lpm | |
| ec-H2O NanoClean® Technology Water Flow | 0.12 / 0.25 / 0.35 gpm 0.45 / 0.95 / 1.32 lpm | |

| Feature | 20 in / 500 mm Single Disk Self Propel | 24 in / 600 mm Dual Disk Self Propel |
|--|--|--|
| Battery System | | |
| System Voltage / Battery Count | 24 Volts / 4 | |
| Batteries | Wet 210 AH Wet 240 AH (Provides longest run time) Sealed AGM 220AH | |
| Battery Run Time (Up to Hours) | 3.1 | 4.0 |
| On-Board Charger | Yes | Yes |
| Off-Board Charger | Yes | Yes |
| Decibel Ratings At Operator Ear | | |
| Standard - dBA | 63.7 | 64.5 |
| Quite-Mode™ - dBA | 59.7 | 61.3 |
| Machine Dimensions and Weights | | |
| Overall Width with Squeegee | 30.1" / 765 mm | 31.2" / 793 mm |
| Length X Width X Height | 55 X 26.5 X 49 Inches 1,397 X 673 X 1,245 mm | |
| Weight (less batteries) | 490 lbs / 222 kg | 495 lbs / 225 kg |
| Weight (with batteries) | 725 lbs / 329 kg | 730 lbs / 331 kg |
| Product Backing | | |
| Warranty | 10 years Rotomold - 3 years Parts 2 years Labor - 6 months of Trip | |

Specifications are subject to change without notice.

