

**NOBLES****Strive™ w/ReadySpace specifications**

Solution System	ReadySpace	Restorative Extraction
Solution tank capacity	21 gal / 72 L	
Nominal solution flow rate	0.33 gpm / 1.3 L / min	1 gpm / 3.8 L / min
Solution pump – psi	100 psi / 6.9 bar	
Nozzle configuration	(2) Quick release nozzles	
Recovery System		
Recovery tank capacity	21 gal / 72 L	
Vacuum shoe size	22 in / 560 mm	23 in / 580 mm
Airflow	65 cfm / 1.84 m ³ per min	
Waterlift	120 in / 3050 mm	
Vacuum motor Hp	(2) 0.64 HP / 0.48 KW	
Vacuum motor stages	3 stage	
Productivity		
Recommended cleaning speed	100 fpm / 30.5 mpm	50 fpm / 155 mpm
Maximum per hour	13,200 ft ² / hr / 1,226 m ² / hr	5,500 ft ² / hr / 510 m ² / hr
Typical range per hour	6,000-10,000 ft ² / hr 560 – 930 m ² / h	2,000-4,000 ft ² / hr 185 – 370 m ² / hr
Brush System		
Roller / Brush length	22 in / 560 mm	
Roller / Brush material	Nylon	
Motor Hp	(2) 0.625 HP / 0.315 KW	
Motor RPM	700	
Drive System		
Top transport speed	Up to 250 fpm / 76 mpm	
Max. ramp while cleaning	3 degree	
Max. ramp while transporting	11 degree	
Transaxle Hp	0.2 HP / 0.104 KW continuous	
Power System		
System voltage	24 V	
Total power consumption	65 amps	
Battery run time	2.5 hours	
Battery configuration	4-6 volt 235 AH batteries	
Roller / Brush circuit breaker	17 A	
Drive circuit breaker	20 A	
Dimensions / Weight / Sound level		
Length	60 in / 1520 mm	
Width	28 in / 710 mm	
Height	42 in / 1070 mm	
Net weight	590 lb / 268 kg (includes batteries)	
Sound Level	72 dBA	
Warranty	3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks. Please contact the company for more warranty information.	