



T5 Specifications | Cylindrical Walk-Behind Floor Scrubber

| Scrubbing System | | |
|---|---|---|
| Cleaning path (2 paths available) | 26 in / 650 mm | 32 in / 800 mm |
| Solution tank capacity | 22.5 gal / 85 L | 22.5 gal / 85 L |
| Productivity (per hour) | | |
| Theoretical max | 28,600 ft ² / 2,700 m ² | 35,200 ft ² / 3,300 m ² |
| Estimated actual* (conventional) | 19,200 ft ² / 1,790 m ² | 24,000 ft ² / 2,200 m ² |
| Estimated actual* (ec-H2O NanoClean™) | 21,000 ft ² / 2,000 m ² | 26,250 ft ² / 2,400 m ² |
| Solution flow rates | | |
| Standard | 22 gpm / .83 lpm | .33 gpm / 1.25 lpm |
| Optional | .33 gpm/ 1.25 lpm | .44 gpm / 1.66 lpm |
| Conventional Option | .25, .35, .45 gpm / .95, 1.3, 1.7 lpm | .30, .40, .50 gpm / 1.1, 1.5, 1.9 lpm |
| Scrub motors | (2) 0.63 hp / 0.47 kW | |
| Scrub motor speed | 1500 rpm | |
| Brush / pad down pressure | 40, 80 & 120 lb / 18, 36 & 54 kg | |
| Brush quantity & size | (2) 25in x 6 in / 635 x 152 mm | (2) 31 in x 6 in / 787 x 150 mm |
| Recovery System | | |
| Recovery tank capacity | 27 gal / 102 L (Includes demisting chamber) | |
| Vacuum fan | | |
| Motor | 0.85 hp / 0.640 kW | |
| Stages | 3-stage | |
| Water lift | 62 in / 1,575 mm | |
| Propelling & Power System | | |
| Propel speed (variable to) | | |
| Transport | 2.7 mph / 4.3 km/h | |
| Scrubbing | 2.5 mph / 4.0 km/h | |
| Batteries (24 V system, charger included) | | |
| Standard / run time** | (4) 6V, 235 AH / Up to 5 hours | |
| Optional Sealed (AGM) / run time** | (4) 6V, 200 AH / Up to 4 hours | |
| Gradeability (ramp climb) | | |
| Scrubbing / transporting (full) | 3.0° / 5.0° | |
| Trailer ramps (empty) | 11° | |
| Speed control | Top Speed Potentiometer & Variable Speed Trigger | |
| Dimensions / Weight / Sound level | | |
| Length | 55 in / 1,400 mm | |
| Width | | |
| Body | 23 in / 580 mm | |
| Scrub head | 28 in / 710 mm | 34 in / 860 mm |
| Squeegee | 41.3 in / 1,050 mm | 46.6 in / 1,180 mm |
| Height | 44 in / 1,120 mm | |
| Net weight | | |
| Less batteries | 357 lb / 162 kg | 365 lb / 166 kg |
| With batteries (4) 6V 235 AH | 621 lb / 282 kg | 629 lb / 285 kg |
| Minimum aisle turn: | 62 in / 1,575 mm | 64.5 in / 1,640 mm |
| Sound level*** (operator's ear) | 68 dBA | |
| Warranty | 3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks. | |

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Run times are based on Continuous Scrubbing Run Times.

*** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA