



Strive® Compact

Cord-electric, ReadySpace® specifications



Brush Drive System

Roller diameter	4 in / 110 mm
Roller length	15 in / 380 mm
Roller motor power (2 motors)	.3 hp / .22 kW (each)
Roller RPM	450 rpm
Motor RPM	1600 rpm

Chassis / Body Construction

Chassis construction	Cast aluminum frame, rotational molded tanks and injection molded plastic cover
Wheel descriptions	8 in / 200mm

Vacuum System

Airflow at orifice	99 cfm / 2.8 m ³ /min
Vacuum motor amps	7.1 amps/ 3.6 amps
Vacuum motor power	1.2 hp / .89 kW
Vacuum motor stages	2 stage
Sealed waterlift	86 in / 2,180mm

Dimensions (Handle folded flat for storage)

Length	30 in / 750 mm
Machine Width	19 in / 490 mm
Height	28 in / 710 mm
Net weight	117 lb / 53 kg

Solution & Recovery System

Solution tank capacity	5 gal / 19 L
Recovery tank wet capacity	5 gal / 19 L
Spray jet count	1-quick connect

Power Consumption

Amps	11 amps / 5.5 amps
Voltage	120 V / 230 V
Watts	1320 watts
Cord	50 ft / 15 m
Electrical Safety Approvals	ETL Tested for UL & CSA Standards

Pump System

Solution pump pressure	65 psi / 4.48 bar
Solution pump amps	.5 amp / .25 amp
Solution pump flow rate	.2 gpm / .76 L/min

Sound Level *

Decibel ration @ operators ear	69 dBA
--------------------------------	--------

Warranty

3 years/2500 hrs on parts and labor.
10 years on rotationally-molded polyethylene tanks.
Please contact your Nobles representative for additional warranty details.

* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA